

Standard/Moderate Duty Stationary Bracket Assemblies

Stationary Bracket Mount No-Slack® 6000, 7000 & 7000CC BSL



6000 7000 7000CC Clean
50,000 pounds vertical load 55,000 pounds vertical load 55,000 pounds vertical load
Connect

6000 BSL Part Number	7000 BSL Part Number (Add 39 lbs)	7000CC BSL Part Number (Add 42 lbs)	Fifth Wheel Height	6000 Weight
SL6BSL5375	SL7BSL5375	SLCBSL5375	5-3/8"	226 lbs
SL6BSL5875	SL7BSL5875	SLCBSL5875	5-7/8"	228 lbs
SL6BSL6875	SL7BSL6875	SLCBSL6875	6-7/8"	233 lbs
SL6BSL7875	SL7BSL7875	SLCBSL7875	7-7/8"	239 lbs
SL6BSL8875	SL7BSL8875	SLCBSL8875	8-7/8"	246 lbs
SL6BSL9875	SL7BSL9875	SLCBSL9875	9-7/8"	253 lbs

Typical left hand model shown in chart.

Options (see pages 6-7)

Features

- BSL fifth wheels are ideal for applications where axle weight, bridge length and kingpin settings remain constant
- BSL brackets are welded directly to the mounting base on your vehicle to save weight and cut costs
- Rapidly gaining in popularity due to weight savings, simplicity of design and overall economy

- Right hand (replace **SL** with **SR**)
- Air actuated (replace **SL** with **AA**): add 5 lbs
- Auto-lube left (replace **SL** with **AL**) Auto-lube models are drilled and tapped for lube system (7000/7000CC)
- LST Electronic lock indicator left (replace **SL** with **SLE**) (7000/7000CC)