

Mounting Bracket

Fontaine BSL Weight Savings Fixed Mount Fabricated Bracket

- BSL fifth wheels are ideal for applications where axle weight, bridge length and kingpin settings remain constant
- BSL brackets are welded directly to the mounting base on your vehicle to save weight and cut costs
- Rapidly gaining in popularity due to weight savings, simplicity of design and overall economy

FONTAINE NO-SLACK

6000BSL

Weight savings fixed mount Fabricated plate

Standard/Moderate duty
On highway only
50,000 lbs vertical load
150,000 lbs drawbar pull
Approx top plate weight 220 lbs

Top Plate

Fontaine No-Slack® 6000 Series Stamped Steel

- No-Slack lock self-adjusts to accommodate kingpin wear
 - Switch from trailer to trailer hassle-free
 - Snug, secure connection
 - Reduces shock inputs into frame when braking/accelerating
 - Improves driver comfort
 - Reduces driver complaints
 - Extends service life of components
- Locking trigger helps minimize high-hitching
 - Reduces driver frustration
 - Reduces tractor, trailer and tire damage
 - The industries best defense against false coupling
 - Saves expensive wrecker and clean up bills
- Easy coupling force—only 30 lbs!
 - Less wear and tear on the kingpin
 - Extends service life of drivetrain components
- Pull handle is the easiest to operate in the industry
 - Opens easily with a simple, straight pull of the handle
 - No complicated opening sequence to remember

Top Plate Performance Options

- Retractable Pull Handle— Handle retracts in the "open" position to help drivers avoid tire and fender damage.
- Air actuated In-cab air release valve located on the dash opens the fifth wheel lock only when the tractor parking brakes are set.



www.fifthwheel.com • 800-874-9780 • Email: parts@fifthwheel.com

* See your Fontaine Representative for application details or refer to Application Guide (LT-076) on website
©2019 Fontaine Fifth Wheel • LT-255 • March 2019 R3



